

**TECHNICAL SPECIFICATION**  
**DIN Width (198MM) Tabular Traction Cells**

Overall Height - H (mm) max				295	365	425	490	570	600	710	745
Cell Height - H (mm) max				270	340	400	465	545	575	680	720
Width in MM	Length in MM	No. of position Plates	Capacity weight	DT 50	DT 60	DT 80	DT 90	DT 115	DT 125	DT 140	DT 150
198	47	2	$\frac{ah}{c5}$ kg.	$\frac{100}{6.6}$	$\frac{120}{8.4}$	$\frac{160}{10.1}$	$\frac{180}{12.1}$	$\frac{230}{14.4}$	$\frac{250}{14.8}$	$\frac{280}{17.4}$	$\frac{300}{18.2}$
198	65	3	$\frac{ah}{c5}$ kg.	$\frac{10}{9.6}$	$\frac{180}{11.9}$	$\frac{240}{14.4}$	$\frac{270}{17.2}$	$\frac{345}{20.5}$	$\frac{375}{21.0}$	$\frac{420}{25.7}$	$\frac{450}{26.1}$
198	83	4	$\frac{ah}{c5}$ kg.	$\frac{200}{12.4}$	$\frac{240}{15.6}$	$\frac{320}{18.6}$	$\frac{360}{21.8}$	$\frac{460}{26.3}$	$\frac{500}{27.1}$	$\frac{560}{33.2}$	$\frac{600}{33.9}$
198	101	5	$\frac{ah}{c5}$ kg.	$\frac{250}{16.2}$	$\frac{300}{19.0}$	$\frac{400}{23.1}$	$\frac{450}{26.6}$	$\frac{575}{32.1}$	$\frac{625}{33.3}$	$\frac{700}{40.3}$	$\frac{750}{41.4}$
198	119	6	$\frac{ah}{c5}$ kg.	$\frac{300}{18.0}$	$\frac{360}{22.4}$	$\frac{480}{27.3}$	$\frac{540}{31.4}$	$\frac{690}{38.3}$	$\frac{750}{39.6}$	$\frac{840}{47.7}$	$\frac{900}{49.6}$
198	137	7*	$\frac{ah}{c5}$ kg.	$\frac{350}{20.8}$	$\frac{420}{26.0}$	$\frac{560}{31.6}$	$\frac{630}{36.5}$	$\frac{805}{44.2}$	$\frac{875}{46.0}$	$\frac{980}{55.3}$	$\frac{1050}{57.5}$
198	155	8*	$\frac{ah}{c5}$ kg.	$\frac{400}{23.7}$	$\frac{480}{29.6}$	$\frac{640}{35.9}$	$\frac{720}{41.4}$	$\frac{920}{50.3}$	$\frac{1000}{52.3}$	$\frac{1120}{62.9}$	$\frac{1200}{65.4}$
198	173	9*	$\frac{ah}{c5}$ kg.	$\frac{450}{25.6}$	$\frac{540}{32.4}$	$\frac{720}{39.7}$	$\frac{810}{45.9}$	$\frac{1035}{57.3}$	$\frac{1125}{58.5}$	$\frac{1260}{69.7}$	$\frac{1350}{73.2}$
198	192	10*	$\frac{ah}{c5}$ kg.	$\frac{500}{29.4}$	$\frac{600}{37.0}$	$\frac{800}{44.0}$	$\frac{900}{50.8}$	$\frac{1150}{62.1}$	$\frac{1250}{64.6}$	$\frac{1400}{78.9}$	$\frac{1500}{81.1}$